

Ref: **OD PE PVC PB****Stripper for PE, PVC, Lead, Ø 25 to 80 mm**

ENEDIS No: 07.57.989

Type of cables:

EDR sheath, fluted or smooth



PE



PVC



Lead

**Characteristics:**

Tool made of composite material and stainless steel.

The tool is equipped with an interchangeable blade based on the material and thickness, Quick removal of the blade without tools..

Blade for PE/ PVC ref **MB{XX}-AL**

Available from 0 to 4 mm:

0,2 | 0,4 | 0,6 | 0,8 | 1,0 | 1,2 | 1,4 | 1,6 | 1,8 | 2,0 | 2,2 | 2,4 | 2,6 | 2,8 | 3,0 | 3,2 | 3,4 | 3,6 | 3,8 | 4,0

Example: 2.8 mm thickness, use ref **MB28-AL**Blade for lead tubing (non-cutting) depth 2 mm ref **MB20-PB**.**Dimensions:** 300 x 123 x 70 mm**Weight:** 1,5 kg**Operating principle:**Turn the blade and roller blocks for circular or longitudinal cutting. Use the 3/8" square T-wrench ref **T200 75 NI** for longitudinal cutting.

Allows straight cutting over long lengths without effort.

Use the retractor, ref **ECARTE DT** remove the outer sheath.Tool **OD PE PVC PB** supplied alone comes with:

- One External square T wrench **T200 75 NI**.
- One lead blade doubles cutting **MB20PB2**.
- One blade **MB20-AL**. (delivered by default with the possibility to modify it on request)

Ref: **KIT OD PE PVC PB****Includes the following accessories:**

Reference	Qty	Description	Weight
OD PE PVC PB	1	Stripper for PE, PVC, Lead, Ø 25 to 80 mm	1940 g
		1 T200 75 NI External square T wrench 3/8"	
		1 MB20-AL PE, PVC blade depth 2 mm	
		1 MB20PB2 Lead blade doubles cutting (no-cutting) depth 2 mm	
MB{XX}-AL	2	PE, PVC blade (indicate the desired depth)	
ECARTE DT	1	Retractor (Lifting the outer sheath of POPY and NIKOL (UTE C33 - 226) type cables)	
SAC KT	1	Thermoplastic case 360 x 170 x 60 mm	

**MB{XX}-AL****MB20PB2****Operations:**

Circular cut



Blade and roller orientation



Engage the driving key



Fast and effortless longitudinal cutting



Remove sheath with the retractor